

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-332866

(43)Date of publication of application : 30.11.2001

(51)Int.Cl.

H05K 3/46
H01L 23/12
H01L 25/04
H01L 25/18
H01L 25/10
H01L 25/11
H05K 1/11
H05K 3/40

(21)Application number : 2000-152621

(71)Applicant : MATSUSHITA ELECTRIC IND CO LTD

(22)Date of filing : 24.05.2000


(72)Inventor : SHIRAISHI TSUKASA
KOMATSU SHINGO
HAYASHI YOSHITAKE
YUHAKU SEI

(54) CIRCUIT BOARD AND METHOD OF PRODUCTION

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a circuit board in which high density mounting can be effected without lowering the containing rate of wiring.

SOLUTION: Containing rate of wiring is enhanced by forming an auxiliary wiring pattern 108 in a component surface region not pertaining to external connection of an electronic component 105 provided in a board, and connecting the auxiliary wiring pattern 108 electrically with wiring patterns of board 103, 102 thereby using the auxiliary wiring pattern 108 as the wiring patterns of board 103, 102.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision
of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office